

Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name

Ferroloid- 1.

Article-no

.

Product/Article	Diameter(mm)	Packaging (kg)	Part Number
Ferroloid- 1	2.5	1	YBD1812102
Ferroloid-1	3.2	2	YBD1812103
Ferroloid-1	4.0	3	YBD1812104

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type SMAW Cast Iron covered electrodes (non Barium containing) Classification: AWS SFA A5.15 (or

other)

Use Electric arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Linde Bangladesh Limited

Street address Corporate Office, 285 Tejgaon Industrial Area

Dhaka-1208 Bangladesh.

Telephone +880.2.8870322-27

Fax +880.2.8870336/+880.2.8870329

Email customer.service.bd@linde.com

1.4 Emergency telephone number

Available outside office hours Yes

162

Emergency phone number +8

+880.1711.404191

Other

Additional product information

 $Web\ site: www.linde-gas.com.bd$



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (CE) 1271/2008 [CLP] applicable

2.2 Label elements

Not applicable

2.3 Other hazards

This product contains: Nickel as classified as sensitising and limited evidence of carcinogenic effect. The form of this product does not contribute to a hazard classification of the product.

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

Alloy core wires	%C	%Si	%Mn	%Ni	%Cu	%Fe
CAS number	7440-44-0	7440-21-3	7439-96-5	7440-02-0	7440-50-8	7439-89-6
Ranges	0 to 0.25	0 to 0.25	0 to 1.0	0 to 99	0 to 35	balance
Hazard Classification				Carc.Cat3, R40-R43		
67/548/EC				S⊗(2-) 22-36		
Hazard				Carc2,H351		
Classification 1272/2008				Skin sens 1 H317		
127272000				11317		

Flux coating	%	CAS No.
Aluminium powder Pyr Stab.	1-3	7429-90-5
Limestone and/or Calcium Carbonate	0 to 25	1317-65-3



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Graphite		
(total inhalable dust)	0 to 15	7440-44-0
(respirable dust)		
Strontium Carbonate	0 to 35	1633-05-2
Cellulose		
(total inhalable dust)	0 to 10	9004-34-6
(respirable dust)		
Starch		
(total inhalable dust)	0 to 15	9005-25-8
(respirable dust)		
Inorganic Fluorides (as F)	0 to 25	16984-48-8
Nickel and its inorganic	0-15	7440-02-0
compounds		
(soluble, as Ni)		
(insoluble, as Ni)		
lron powder	0 to 15	7439-89-6
Rutile/Titanium Dioxide		
(total inhalable dust)	0 to 5	13463-67-7
(respirable dust)		
Silicate Binders	0 to 35	1344-09-8
Others		

Section 4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	$\label{thm:lem:index} IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for a complex of the property $
	breathing. Call a physician if symptoms occur.
Skin contact	Burns should be treated by a doctor.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
	easy to do. Continue rinsing. Burns from radiation, see doctor.
Ingestion	Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for fire fighters

Special protective equipment for fire

Wear self -contained breathing apparatus

fighters

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

For *Personal protection* see section 8. For *Disposal* see section 13. For *Environmental precautions* see section 12. For *Precautions for safe handling* see 7.1.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions

Ensure adequate ventilation for the welder and others. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Remove all flammable materials and liquids before welding.



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

General hygiene Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store $away from \ chemical \ substances \ like \ acids \ which \ could \ cause \ chemical \ reactions.$

7.3 Specific end use(s)

Welding process.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	WEL ² 8hr TWA	STEL² 15min TWA	Hazard Classification 67/548/EC	Hazard Classification (GHS) 1272/2008
Iron oxide fume (as Fe)	1309-37-1	5	10		
Manganese and its inorganic compounds (as Mn)	7439-96-5	0.5		R20/R22	H332/H302 Acute Tox.4
Copper					
(fume)	7440-50-8	0.2			
(dust and mist)		1			
Nickel and its inorganic compounds (water soluble)		0.1		R40/R43/ R49/R53	H350i/H351 Carc 2 /H317 Skin sens 1
(water insoluble)		0.5			/H413 Aquatic Ch.4
Silica, amorphous					
(total inhalable dust)	-	6			
(respirable dust)		2.4			
Titanium dioxide					
(total inhalable dust)	13463-67-7	10			
(respirable dust)		4			
Calcium Oxide	1305-78-8	2			
Calcium Silicate					
(total inhalable dust)	1344-95-2	10			
(respirable dust)		4			
Fluoride, inorganic (as F)	16984-48-8	2.5			
Carbon Monoxide	630-08-0	30ppm	200ppm		
Carbon Dioxide	124-38-9	5000ppm	15000ppm		
Nitrogen dioxide (NO ₂)	10102-44-0	0.5 ppm ³	0.95 ppm ³		
Ozone (O ₃)	10028-15-6		0.2 ppm		
Nitrogen monoxide (NO)	10102-43-9	0.5 ppm ³	0.63 ppm ³		



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

8.2 Exposure controls

Environmental Exposure Control - Refer to section 6 of this SDS

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume concentrations
	within safe limits.
Eye / face protection	Wear eye protection appropriate for welding.
Safety gloves	Skin contact should be avoided to prevent possible allergic reactions.
Other skin protection	$We ar body\ protection\ which\ helps\ to\ prevent\ injury\ from\ radiation,\ sparks\ and\ electric\ shock.$
Respiratory protection	$\label{thm:confined} \textbf{Use respiratory equipment when welding in a confined space}. We ar protective clothing and eye$
	protection appropriate to arc welding.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

9.1 Information on basic physical and chem	nical properties
Appearance, colour	Grey
Appearance, physical state	Rod
Auto-ignition temperature	Not applicable
Auto-inflammability	Not auto-flammable
Decomposition temperature	Not applicable
Evaporation rate	Not applicable
Explosive properties	Not explosive
Flammability (solid gas)	Not applicable
Flash point	Not applicable
Form	Metal rod with flux covering
Initial boiling point and boiling range	Not applicable
Melting point / Freezing point	Not applicable
Odour	Odourless
Odour threshold	Not applicable
Oxidising properties	Not applicable
Partition coefficient: n-octanol / water	Not applicable
pH value	Not applicable
Relative density	Not applicable
Solubility	Not applicable
Solubility in water	Insoluble
Upper / lower flammability or	Not applicable



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

explosive limits

Vapour density Not applicable

Vapour pressure Not applicable

Viscosity Not applicable

9.2 Other information

Not applicable

Other

Density 7,98 g/cm³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not applicable

10.2 Chemical stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Not applicable

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/20	008)	Concentration of classified fume components
Aluminium oxide (AI)	1344-28-1	-	-	-	<0.1 to 1.3
Barium (Ba)	7440-39-3	-	-	-	<0.1 to 0.4
Bismuth oxide (Bi)	12640-40-3	-	-	-	≤0.1
Calcium (Ca)	1305-78-8	-	-	-	0.8 to 23.3



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

		R22: Harmful if swallowed	Acute tox 4 (oral)	H302	≤0.1
Cobalt oxide (Co)	1307-96-6	R43: May cause sensitisation by contact	Skin sens. 1	H317	
Chromium III		R45: May cause cancer R35: Causes severe burns	Carc. 1B Skin Corr. 1A	H350 H314	≤0.1
compounds (as Cr)	24613-89-6	R43: May cause sensitisation by skin contact	Skin Sens. 1	H317	
Copper oxide (Cu)	1317-38-0	-	-	-	<0.1 to 11.4
Iron oxide (Fe)	1332-37-2	-	-	-	1.1 to 29.6
Potassium (K)	7440-09-7	R34: Causes burns	Skin Corr. 1B	H314	0.4 to 11.3
Lithium (Li)	7439-93-2	R34: Causes burns	Skin Corr. 1B	H314	≤0.1
Magnesium oxide (Mg)	1309-48-4	-	-	-	0.1 to 4.0
Manganese (Mn)	7439-96-5	-	-	-	0.1 to 4.0
		Molybdenum trioxide R36/37: Irritating to eyes	Molybdenum trioxide Carc. 2	H351 H319	≤0.1
Molybdenum (Mo) 7439-98-7	and respiratory system R40: Limited evidence of carcinogenic effect	Eye Irrit. 2	H335		
			STOT SE 3		
Sodium (Na)	7440-23-5	R34: Causes burns	Skin Corr. 1B	H314	0.1 to 23.4
		R40: Limited evidence of carcinogenic effect	Carc. 2	H351	0.1 to 10.3
		R43: May cause	Skin sens 1	H317	
		sensitisation by skin contact	STOT RE 1	H372	
Nickel (Ni)	7440-02-0	R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation			
		R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment			
Lead (Pb)	7439-92-1	-	-	-	0.1
Silicon (Si)	7440-21-3	-	-	-	1.1 to 4.2
Titanium dioxide (Ti)	13463-67-7	-	-	-	<0.1 to 0.7
Vanadium (V)	7440-62-2	-	-	-	≤0.1
Zinc (Zn)	7440-66-6	-	-	-	<0.1 to 0.5



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Fluoride (F-) 16984-48-8 0.6 to 12.3

Classification	H phrase	Text
Skin corrosion/irritation: Category 1B	H314	Causes severe skin burns and eye damage
Skin sensitiser Category 1	H317	May cause an allergic skin reaction
Carcinogenicity: Category 1B	H350	May cause cancer
STOT Repeated Exposure Category 1	H372	Causes damage to organs through prolonged or repeated exposure

The classification information above relates to the fume during use

Analysis wt %	
Al 0.1 to 1.3	Ni 0.1 to 10.3
Ca 0.8 to 23.3	
Fe 1.1 to 29.6	
K 0.4 to 11.3	
Mg 0.1 to 0.4	
Na 0.1 to 23.4	

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary oedema

and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation of the nose,

throat or eyes.

Irritation Not applicable

Corrosive effects Not applicable

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not applicable

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity Not applicable Reproductive toxicity Not applicable

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not applicable

12.3 Bio accumulative potential

Not Available

12.4 Mobility in Soil

Not applicable

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

Not applicable



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations Dispose of any product, residue or packing material according to national and local regulations. Spent;

fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code None

14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class (es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Other

Dangerous goods No

Section 15. REGULATORY INFORMATION

 $15.1\,Safety, health \, and \, environmental \, regulations \, / \, legislation \, specific \, for \, the \, substance \, or \, mixture.$



Version number: 4

Replaces SDS: 2009-11-23

Issued: 2015-02-05

EU regulations

National regulations

The product does not need to be labelled in accordance with EC directives or respective national laws.

None

15.2 Chemical safety assessment

Not applicable

Section 16. OTHER INFORMATION

References to key literature and

Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).

data sources

Regulation (EC) No 1272/2008 of the European Parliament and of the Council.

EH40/2005 Workplace exposure limits.

The Waste regulations 2011 No.988

KIFS 2005:7

www.prevent.se

C&L Inventory database

Annex VI CLP Regulation (EC) 1272/2008

Phrase meaning

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

Other

Manufacturer's notes

Read this Safety Data Sheet carefully and become aware of hazards implied and the safety

information.

End of document